

ecoGreen

Eco, sustainable, 100% recycled.

EXTRUDED ACRYLIC SHEETS

ECOGREEN sheets are produced from 25% to 100% of post industrial extruded grinded PMMA .
Only pure clear PMMA.

Available glossy surface, in several patterns and colors.

Our sheets are ecofriendly, recycled and completely recyclable.

Technical Information Acrylic Sheet ECOGREEN

PROPERTY	MEASURE UNIT	Method ASMT	Method DIN	Method ISO	PMMA
Ultimate Tensile Strength	MPA	638	53455	527/66	70
1% offset yield stress σ_s	%	638	53455	527/66	5
Tensile Modulus Ez	MPA	790	53457	178/75	3200
IZOD impact strength	Kj/m ²	256	-	180/61	1,2
VICAT softening temperature B/50	°C	1525	53460	306/74	108
Heat Distortion Temperature - HDT	°C	648	53461	75	100
Density	g/cm ³	792	53479	1183	1,19

Ecogreen extruded acrylic sheets, a circular choice for a green planet.

AMBR
POLYMER

AMBRO POLYMER S.r.l.
Via Risorgimento, 29
21020 Bodio Lomnago (VA) - Italia
Tel. +39 0332 947121 - info@ambropol.com
www.ambropol.com

